

CAP: Goals, Architecture, and Intended Scenarios

Jamie Stephens

Morphism (morphism.com)

js@morphism.com

September 19, 2026

Abstract

Continuing work by coding agents requires retained state, execution controls, shared artifacts, and procedures for checking and using results. CAP (Communicating Agent Processes) provides these facilities through a Go runtime with persistent agents, managed programs, private execution environments, and local or remote coordination. CAP’s design places durable execution and general coordination in the runtime, while application instructions and agent-written programs determine research methods, supervision, and publication. This report describes that division, five intended scenarios, and the harness implementations considered during development. It relates the design to recorded tests of research groups, method reuse, recovery, and process capacity. Those tests demonstrate small-group execution and expose failures in compaction and final publication. A network of 100,000 to 1,000,000 or more agents remains a deployment objective. The remaining work concerns sustained research quality, ownership during network failure, context costs, and distributed capacity under application load.

1 Purpose and design goals

CAP’s design places durable execution and general coordination in the runtime, while application instructions and agent-written programs determine research methods, supervision, and publication. The project aims to keep a general coding agent in Go that can work on files, execute commands, browse sources, create other agents, and develop programs and services. The same operations support an interactive coding task and a continuing research assignment. Pi supplies the behavioral reference for the native agent loop. The ACE library supplies shared-object coordination. Tungsten supply-chain research supplies an application that exercises the facilities through instructions, source material, and working conventions [4, 5].

The intended outcome is a system in which a group can retain its work, divide responsibilities, inspect failures, and use another participant’s verified results. A continuing assignment may outlast a model request, a run, a controller process, or its original owner. CAP therefore separates conversation state, execution state, artifacts, and management authority. The application records the question under investigation, the evidence supporting its conclusions, and the unfinished work that a successor must receive [4, 7].

This report describes the CAP source revision identified in the source record. Implemented behavior comes from the operator and agent manuals, source checks, and the development record.

The earlier research trials describe prior runtime revisions. Their summaries use CAP terminology while preserving dates, outcomes, failures, and interventions. The cited test accounts preserve their evidence summaries. Their changing prompts, settings, and source conditions constrain comparisons. The CAP verification record identifies newly executed tests [6, 8, 3].

CAP’s expanded name refers to Hoare’s *Communicating Sequential Processes* [1]. Concurrent CAP agents communicate through ACE shared objects, pattern matching, reads, and atomic takes. ACE defines the implemented coordination semantics. Applications choose message schemas, responsibility, and result-consumption procedures.

CAP uses the `github.com/jsmorph/cap` module and the `cap`, `capctl`, `cap-worker`, and `cap-forge` commands. CAP requires format markers on its journals and on repository, group, and retrieval storage. The runtime rejects earlier formats and begins with newly created state. Reopening and recovery apply to CAP-created state [6, 3].

1.1 Runtime objects and responsibility

Separate agent, run, process, and world records determine what survives an interruption and what a caller must inspect before continuing work (Table 1). An idle agent can have an unfinished sleeping or interrupted run. A completed run supplies an execution outcome, while the correctness and completeness of its artifacts require application checks [5].

Object	Meaning in CAP
Controller	A CAP process that manages agents, retained records, execution capacity, and local or peer APIs.
Agent and session	An agent has an identity, conversation, input queue, settings, and usage. Its session retains those records across runs and reopening.
Run	An identified period of assigned work, with retained input associations and a completed, failed, or cancelled outcome. One agent executes at most one run at a time.
Wake	Retained scheduled input with an ID, message, and due time. Delivery queues the message to resume the agent’s work within its execution limits. Reopening restores pending delivery.
Managed process	A command supervised by CAP, with retained output and lifecycle records. It can continue while its owning agent is idle.
World	The filesystem, installed tools, process limits, and network environment selected for execution. A child can share a world or receive a private Podman container.
Monitoring assignment	An application record of continuing responsibility for a topic, source, entity, or relationship. Its scope and evidence can persist across agents and runs.

Table 1: Runtime objects and the application-level monitoring assignment.

The controller provides persistence and operations. The application chooses work decomposition, artifact formats, source policies, review criteria, and stopping conditions. Agent-written code can implement repeated collection, completion notices, or publication using the same operations available to model tools. This division permits an application to revise its procedure without changing the runtime. It also assigns responsibility for application correctness: the collector, reviewer, and publisher must preserve the evidence and dependencies required by their assignment [4, 7, 9].

2 Intended scenarios

2.1 Coding and repository work

A coding assignment begins with a repository, a requested change, and applicable instructions. An agent reads the project, edits files, executes builds or tests, and retains the resulting artifacts and command output. A parent can assign a bounded investigation or implementation to another agent, specify ownership of files, and request a review before incorporating the result. Separate workspaces or Git worktrees provide application-selected separation when participants edit concurrently [5, 6].

CAP includes a repository service for Git transport, issues, pull requests, reviews, and collaborator permissions through a supported subset of GitHub APIs usable by the ordinary `gh` CLI. Recursive groups express shared access. Agents can use those facilities to propose a tool revision, review an exact commit, and retain the decision. Acceptance of a code change depends on the task’s tests and review evidence. The service retains the collaboration record [6].

2.2 Bounded collaborative research

The initial tungsten assignment asks a main agent to produce a cited supply-chain report. It creates three researchers covering mining, processing, and consumption. Each researcher writes a result file with its sources and sends the main agent a small ACE object identifying that file. The main reads the contributions, checks consequential claims, requests focused follow-up within the remaining time, and writes the completed report. The application supplies these roles and publication conventions in its prompt [10].

A mine’s announced capacity, permitted production, dispatched concentrate, a processor’s receipt, and a customer’s qualified product describe different events. A cited relationship must identify the parties, material form, time, and supporting statement. Repeated coverage of one announcement retains that common origin. Incomplete source access leaves a stated gap. The prompt reserves time for review and final output because a finished researcher and an available file still require synthesis by the main agent [10, 11].

The pattern assigns questions, retains the evidence behind each answer, and integrates checked contributions into an identified final artifact. Its success criteria include the quality of the answer, source coverage, and publication before the deadline. Execution success alone establishes that the program finished its assigned run.

2.3 Continuing situational awareness

The longer-term application maintains an account of events, changes, and evidence across many topics. A tungsten assignment might follow a mine, converter, customer, transport route, or regulator. An agent-written collector checks sources on a schedule and retains responses. A detected change can trigger a bounded investigation into quantities, affected products, alternative capacity, or dependent customers. The resulting assessment links its conclusions to observations and records questions that require further work [7].

An observation needs source identity, retrieval time, retained content, and an identity distinct from its content hash. A source can return old bytes after an intervening correction, so the new retrieval remains a new observation. Event time and publication time require separate fields when known. Retrieval failure, unchanged content, a maintenance page, and an overdue check have

different meanings for coverage. Historical retrieval can supply evidence for a gap. An unsuccessful archive query leaves the gap unresolved [7, 8].

Collection, review, and publication require separate progress records. The collector records which observations it obtained. The reviewer names the observations it examined and the questions it left open. The publisher identifies the reviewed evidence incorporated in a particular assessment revision. An entry document identifies the current assessment revision and links to its evidence, methods, responsibility records, and unfinished work. A processor-level assessment can contribute to regional and supply-chain assessments, with each broader conclusion retaining its supporting links. This arrangement exposes a current collector feeding a delayed review or a stale publication [7, 11].

The geographic deployment objective is 100,000 to 1,000,000 or more agents across many CAP processes. Saved agents, loaded agents, active runs, simultaneous model requests, and containers are separate capacity measures. Routine scheduling and supervision belong near the work, with bounded calls between controllers. Assignment storage, distributed ownership, cross-host telemetry, and capacity under sustained research remain engineering questions in the proposal [7, 12].

2.4 Shared methods and continuing learning

Agents can develop collection programs, source-review procedures, executable checks, and short skills while working on an assignment. A skill is a retained procedure that another agent can read and apply. CAP installs an indexed collection beside its agent manual and permits agents to publish further procedures through files, ACE notices, and repositories. Executable tools have descriptors and entry points that another participant can inspect and run in its own environment [5].

Learning in this report means retaining and revising procedures, programs, and evidence for later use. A proposed improvement has a version, a stated reason, and a check by a consumer. The consumer may expose a defect, adapt the method to different evidence, or obtain the same result with the earlier version. That last outcome leaves the new version’s benefit uncertain. The September 18 trials exercised this distinction by preserving both procedure versions and a fresh reader’s counterexample [13].

Shared retrieval databases can store short findings or procedures with source and revision metadata. Retrieval supplies candidate material for inspection. A correction needs to remain discoverable alongside the superseded record and its evidence. Retirement also requires artifact transfer: deleting an agent ends its file URLs even when the workspace survives. A successor must copy, check, and republish material whose continued availability the assignment requires [5, 7].

2.5 Agent-written services and mixed backends

An agent can write and start a service, publish its interface, and let other agents or programs use it. Managed processes retain output and can have bounded restart policies. Examples include a source collector, a document-query service, and a program watching child-run outcomes. Service readiness, checkpoint formats, and the meaning of a successful response belong to the application. The runtime supplies execution, inspection, stopping, retained events, and access to agent operations [5, 8, 9].

CAP can also manage Pi, Codex CLI, and Claude Code as external backends. Each external CLI owns its model loop, tools, and native session. CAP supplies accepted input, lifecycle control, result retention, and supported budgets. Backend capability reports identify differences in steering, accounting, and settings. Native context editing and compaction operate within the native CAP

backend. An application using external agents must account for the controls exposed by its selected adapter [6].

3 Execution, coordination, and retained state

3.1 Interfaces and execution environments

The command line, native model tools, HTTP handlers, and agent-written programs call shared runtime operations. Programs use `capctl` through a controller Unix socket. Their tokens identify the owning agent, and calls enter that agent’s tool accounting and journal. The program interface exposes agent, process, ACE, retrieval, executable-tool, and controller-setting operations. Wake and session-context tools have separate interface availability, which a program must check [4, 5].

Local callers and remote peers reach the controller’s runtime operations through the interfaces in Figure 1. A private Podman world retains its filesystem and installations for reopening. Agents sharing a world share permissions, installed tools, ports, and process limits. Other worlds’ mounted workspaces are read-only. A controller can serve workspace files as ordinary HTTP downloads and directory listings. Its browser interface permits a human to inspect retained conversation, send input, stop work, create agents, and reopen saved sessions [6, 5].




Figure 1: Interfaces and responsibilities within one CAP controller. Local callers use the CLI, native tools, or program API. Remote peers use HTTP. Interface-specific operation lists determine which calls each exposes.

Peer HTTP assumes trusted tailnet participants. The receiver accepts the caller’s supplied ACE identity and applies its local operation and access rules. The destination supplies execution resources and credentials for a remote agent. This trust assumption constrains deployment: access to the peer listener conveys authority that must be controlled by the surrounding network. Cross-host tests remain outstanding in the current agenda [6, 12].

Workspace HTML shares the operator interface’s origin. An HTML artifact can therefore call operator APIs when the user opens it in a browser. A Chromium probe read the agent list through

such an artifact, and the CAP source retains the authorization and file-serving behavior used in that probe. Separating artifact content from operator authority remains an open security issue [2].

3.2 Input, results, and recovery

CAP retains accepted input and its run association before acknowledgment. A caller can retry a saved input ID with the same content and delivery mode to retrieve the original receipt. Steering joins unfinished work at the backend’s input boundary. Queued input receives a separate run association. Native agents finish the current tool batch before consuming steering. These boundaries make input acceptance and model attention distinct events [4, 5].

Completed native model responses enter the journal before tool dispatch. Tool intent and tool result have separate records. Partial streamed tool arguments remain provisional. On reopening, CAP reconstructs input, context, settings, usage, and wakes from retained records. An interrupted external effect can remain uncertain and require acknowledgment after inspection. Recorded effects and unknown outcomes therefore survive recovery with different meanings [4].

A result reference includes the controller, agent ID, and run ID. Selecting the run preserves the meaning of a result after the same agent accepts later work or unloads. Waiting for an agent to become idle can return during sleep or interruption. Waiting for a selected run addresses its terminal outcome. Cancelling a wait leaves the work running. An explicit stop targets the execution [5].

A process restart policy can restore unfinished supervision when its owning agent reopens. The restarted command reconstructs its application state from files or other retained storage. Ownership transfer changes which identity can manage an agent while preserving its usage, workspace, and retained work. The current owner can delegate lifecycle controls. A successor’s management authority and the publisher’s choice of review inputs remain separate application concerns [4, 5, 11].

3.3 ACE and artifact exchange

CAP embeds the ACE Go API through the pinned `jsmorph/ace` module [14]. Each controller has one ACE shared-object store, and each agent has a stable caller identity. `ace_out` publishes a JSON object. `ace_rd` reads a matching object while retaining it. `ace_in` takes a matching object and removes it. Matching, access rules, expiry, and cancellable waits follow ACE’s semantics. Each operation can select a local store or a remote controller [5].

CAP’s configured object-size limits favor short coordination records. A producer first writes a substantial report or data file, then publishes its location and identifying metadata. Taking the notice preserves the file. A remote file URL also supplies an access path when a local filesystem path has no meaning to the recipient. Applications choose message schemas, artifact versions, and duplicate-handling rules [4, 5].

A lost response to a remote publication or take can leave its outcome unknown. Automatic ACE input reception can lose a message if the controller stops after removing it from ACE and before appending it to the receiving input journal. For a completion monitor needing a retained retry receipt, the watch example uses saved outgoing content and an explicit input ID with `agent_send`. Its receipt establishes accepted delivery. A parent still has to inspect and use the result [4, 9].

3.4 Asynchronous user communication

An agent publishes a question or report as an ACE object addressed to a user ID. The browser inbox retains messages and reply state in IndexedDB, keyed by controller instance and user. A question has a stable message ID. Its reply has a stable reply ID and reaches the agent through ACE steering. The selected inbox retries saved replies while a CAP page remains open, until acknowledgment or an explicit pause. Reopening the same inbox resumes pending retries. The agent records the reply before acknowledging it and handles duplicate delivery by reply ID. Reports need no answer [5, 6].

An agent can continue independent work while waiting for an answer. The controller exposes ACE over its peer HTTP listener, and agent-written programs use the same operations through `capctl`. These interfaces permit an agent, child, or supervised program to report progress or request a decision without requiring the user to follow a particular agent’s active run. The application chooses the user ID, message content, reply destination, and handling of unanswered questions [5].

3.5 Budgets and capacity

Native agent budgets can bound lifetime, input tokens, output tokens, tool calls, model attempts, and allocated child creation. Usage persists across runs, context changes, and reopening. Token accounting uses provider reports. An in-flight request can exceed its allowance, and an interrupted request can leave its usage unknown. With a token limit, unknown usage blocks further model calls until the recovery policy permits continuation. Reported totals retain the uncertainty [5].

The optional child-creation pool allocates a cumulative allowance. Creating a child consumes one slot plus the pool assigned to that child. For example, ten available slots permit one child with four delegated slots and leave five slots with the parent. The creation record retains the reservation before dispatch. Retries reuse it, and failures or deletion retain the expenditure. A remote destination accounts for the child’s allocation locally. Budget replacement can change these allowances, so the pool is a cooperative task limit [5].

Controller limits separately govern resources such as simultaneous model requests, tools, processes, and retained storage. Waiting releases model-request capacity. Unloading an idle agent releases live resources while preserving its session. These controls permit many saved assignments to use fewer active execution slots. Their value at the proposed network scale requires workload measurements [4, 12].

3.6 Context and application memory

CAP persists application instructions outside editable conversation context and inherits them at child creation. Native sessions support inspection, explicit context replacement, forks, and compaction. A fork copies the selected context into a new identity with fresh usage accounting and a separate assignment. Its environment and file ownership follow ordinary creation rules [4, 5].

Classic compaction follows Pi’s summary-and-recent-history method. CAP summarizes older history using a labeled transcript and keeps a suffix of complete exchanges. A cut inside a user turn can require separate summaries of earlier history and the turn prefix. The complete journal remains available. Agent-configured executable hooks can supply a validated replacement or select the configured algorithm. Summary quality, retained size, and time spent producing it affect whether an agent completes its remaining work [5, 15].

The default size trigger counts serialized conversation bytes. The optional token-configured trigger estimates tokens from bytes and includes instructions and tool definitions. Encrypted items and images complicate that estimate. Experimental provider compaction has a separate availability limit: the recorded subscription tests returned HTTP 404, including the September 14 recheck. CAP then exercised classic fallback. The public OpenAI compaction API describes supported request forms and returned replacement context, while the CAP tests establish the behavior of the subscription endpoint used in those runs [15, 8, 27].

4 Harnesses and precedents considered

The reviewed harnesses informed different CAP mechanisms and proposed experiments (Table 2). Revision identifiers delimit the source claims. CAP has no controlled performance ranking against these harnesses [15, 22, 5].

System	Reviewed source	Relevance to CAP
Pi	71dca871bc80 [16]	Primary behavioral reference for agent execution, tools, steering, sessions, and classic compaction. Also an external backend.
Codex	c4017a87aacc [17]	Authentication and transport checks, an external backend, and comparison of provider compaction, text summaries, and fresh context windows.
Claude Code	Official documentation [18]	An external backend and documented comparison for older-tool-output removal, summaries, and persistent instructions.
OpenCode	95daf90670b7 [19]	Comparison of recent-turn retention, configurable context allowances, pruning, and summary construction.
Aider	5dc9490bb35f [20]	Comparison of history allowances, background summarization, and weak/main summarizer selection.
OpenClaw	bd2b8414cd7f [21]	Completion capture and delivery, child-assignment boundaries, and prompt-size accounting.
pi-subagents	07bd09e0f93a [23]	Selective claim auditing, activity inspection, completion monitoring, method revision, and cumulative child limits.
Cursor agent swarm	July 20, 2026 report [24]	Candidate experiments in decomposition, decision ownership, independent review, shared procedures, and model cost.

Table 2: Harnesses and agent systems considered during CAP development.

CAP adopted Pi’s separation between completed responses and tool execution, retained native sessions, steering, and a compaction method that summarizes a prefix while keeping recent exchanges. The survey also identified a sizing difference: Pi’s recent-history allowance belongs to a model-sized token budget, while CAP’s byte trigger can leave little room after retaining its tail and summary. Copying an algorithm leaves its operating thresholds and failure behavior to be examined in the receiving runtime [5, 15, 16].

The compaction survey separates four controls for CAP experiments: the trigger, recent-history allowance, summary size, and time spent summarizing. Changing a summary prompt leaves a large retained tail unchanged, while shortening the timeout changes which summaries finish. Proposed replays therefore vary one control at a time and check both retained information and completion of

a subsequent assignment. The source comparison establishes available mechanisms. Their effects on CAP require those measurements [15].

OpenClaw’s reviewed source separates execution completion, captured output, and delivery. It also marks a forked child’s current assignment relative to inherited context and reports contributions to prompt size. The CAP review proposed using existing run reads and durable input to implement a completion monitor, with reporting policy selected by the application. CAP now has an adaptable watch program and bounded activity reads. A prompt-size report remains a proposal. OpenClaw’s delivery paths have finite retry and suspension behavior, which constrains any claim of guaranteed receipt [22, 21, 9, 12].

The `pi-subagents` review led to approved work on activity reads, claim-auditing guidance, completion delivery, and allocated child-creation budgets. CAP’s claim-auditing skill cites the extension’s evidence-auditor prompt as its source. CAP expresses those techniques through general operations and short procedures. Their effect on research quality remains an empirical question, as the successful reuse trial obtained correct conclusions with both compared method versions [5, 23, 13].

Cursor’s published swarm study motivated questions about decomposition, ownership, independent reviewers, shared methods, and role-specific model costs. The cited study changed several mechanisms together. CAP’s ideas document therefore treats their individual contributions as unresolved and proposes comparisons with fixed tasks and budgets [24, 25]. Erlang’s supervision documentation supplies a separate precedent for child lifecycle management and bounded restarts. CAP uses process restart policies and has a proposed application-level takeover procedure. Policy for an unreachable owner remains open [26, 25, 12].

5 Recorded evidence and its limits

5.1 CAP verification

The September 19 CAP checks exercised controlled runtime and backend behavior, retained state, peer operations, Chromium chat and inbox behavior, private and inherited Podman worlds, program access through `capctl`, repository collaboration through `gh`, and RAG storage. Disposable unsupported journals and databases were rejected without changing their bytes. CAP-created state supported reopening and torn-tail recovery. A repeated inference exercise failed during shutdown when ACE returned SQLite’s interrupted-transaction error instead of a context-cancellation error. That unchanged reception path remains an open reliability issue. The verification record retains the passing runs, this failure, and the exercise corrections [3].

A fresh live controller used model `gpt-6-astra` with high reasoning and Codex subscription authentication. Its parent and private child inspected installed instructions and called `capctl`. The child published a file reference through ACE, and the parent checked its contents. The browser answered the parent’s question through the inbox. The parent retained the answer, acknowledged it, checked the requested output file, and published an asynchronous report. Both agents completed, and controller shutdown stopped their private worlds. This bounded exchange verifies the implemented communication path under the recorded conditions [3].

5.2 Research continuity and publication

The September 14 case study followed two groups with four research agents each on one host, using live `gpt-6-astra` inference at high reasoning and controlled fictional tungsten sources. The agents developed collectors and publishers, checked and merged one another’s method revisions, transferred collector management, and continued through eight controller interruptions. Checked collection records preserved the served source revisions. Main assessments became stale: one reviewer stopped after a failed request, successor findings failed to reach a main publisher, and another publication retained an obsolete completion flag [11].

Transferring control of a collector preserved collection, but the new owner’s review output required a corresponding change in publisher input. A subsequent thirty-minute assignment recovered a deliberately failed reviewer and published successor findings through another crash. Its final review arrived after publication had stopped, leaving the entry nine collection cycles behind. A handoff therefore needs evidence of completed collection, review adoption, and publication, each checked against the same assignment [11].

The original groups had six-hour limits. Their drivers recorded about six hours fifteen minutes in UTC and two hours thirty-seven minutes in monotonic elapsed time. Later observations recorded forward UTC steps while guest monotonic and boot clocks agreed. The host cause remained unverified. These records limit duration claims from those tests and require separate clocks in future sustained observations [11, 8, 12].

A later public-source group monitored tungsten-related sources, resumed through a forced crash and an orderly restart, checked predecessor methods, recovered a worker, and retired three workers after preserving their artifacts. Its final collection completed before its cutoff. Two sequential compaction requests delayed publication by about five minutes. The parent then published its fourth assessment revision and updated the entry before the closing deadline. It preserved unresolved archive gaps and reported no material supply-chain claim change within its review scope [8].

The public-source test driver recorded about 119 minutes in UTC and 100 minutes on guest monotonic and boot clocks. Reported inference usage also remained incomplete after interrupted requests. The run supports checked publication and retirement under its recorded conditions. Overnight continuity, replacement of an unreachable owner, and complete cost measurement require further evidence [8, 12].

5.3 Method reuse and outcome observation

The first September 18 method-development trial retained a source-based assessment, worker reports, method versions, and a consumer’s calculation. The parent corrected its children’s invalid model setting and resumed them without operator steering. A late compaction ran for 96 seconds before the outer deadline cancelled it. The final learning record and CLI output remained incomplete [13].

The successor trial supplied later synthetic notices, the earlier method, a larger context threshold, and earlier closing targets. Two fresh readers used different method versions. One constructed two batches with the same aggregate assay and different assays in the qualified subset, demonstrating why whole-batch composition alone could not establish the subset’s composition. The parent reran the calculation and incorporated a final audit. All three children and the parent completed in about 461 seconds. Both method versions supported the checked conclusions, leaving the revision’s necessity unproven [13].

The watcher resumed saved state after a deliberate stop and delivered three distinct inputs once each. Two watches overlapped at completion and generated different notices about that event. The group used its three allocated creation slots without changing the pool. Retained summaries report 45 model attempts, about 1.19 million input tokens including repeated context, and approximately 25,000 output tokens. No compaction occurred. Prompt, task, and context changes prevent attributing the successful closing to one change. Broader benefits from observation and method revision remain unmeasured [13].

5.4 Compaction costs and execution capacity

Earlier monitoring tests recorded replacement contexts of 84–114 KiB under a 128-KiB trigger. Completed compactations consumed about 71% of one 45-minute parent lifetime. A different run using a 256-KiB trigger spent about 31% of its 43-minute lifetime compacting and completed more work. The tasks differed, so these observations identify context and summary costs without isolating an optimal threshold. A controlled comparison needs the same captured context, retained-tail policy, continuation task, and stopping conditions [15].

The September 9 scale test created 1,000 idle host agents, each with one managed process, and exercised concurrent waits and shutdown. A separate variant created 100 private Podman worlds. These tests used empty agent contexts and no model inference. They establish the tested lifecycle capacity on that host and implementation. Sustained model work, browser activity, evidence retention, and cross-host coordination introduce additional loads. The observed Podman network used a /24 subnet, making address allocation another requirement before larger container deployments [28].

6 Outstanding work and evaluation criteria

Publication failures, uncertain ownership, and compaction costs require evaluations that connect runtime behavior to completed application work (Table 3). The distributed-awareness objective also requires measurements across hosts with sustained research loads. The current agenda and source survey identify these remaining evaluations [12, 7, 15].

The present evidence supports a runtime on which small groups can conduct research, construct shared tools, transfer management, and resume retained work. It also identifies publication dependencies, costly compaction, incomplete usage after interruption, and clock uncertainty. The intended distributed system requires those execution facilities to support maintained evidence and current assessments over longer periods and across hosts. Its scale and research-quality claims remain bounded by the tests reported here.

Question	Required evidence
Sustained current assessment	Collected, reviewed, and published observation IDs across long assignments, source outages, controller restarts, and final shutdown.
Ownership under network failure	An approved rule for an unreachable owner, followed by tests of continued old-owner execution, duplicate collection, and reconciliation.
Context cost and continuity	Replays of the same contexts with measured retention, summary latency, failed attempts, preserved corrections, and completed continuation work.
Benefit of shared methods	Fresh consumers on comparable tasks, retained method versions, independent checks, failed transfers, and unchanged outcomes.
Distributed capacity	Separate counts for saved and loaded agents, active runs, model requests, and worlds, with latency, storage growth, recovery, and research freshness under load.
Complete resource accounting	Reported and unknown inference usage, tool and review work, storage, and coordination overhead under fixed task and budget conditions.

Table 3: Open questions tied to measurable application outcomes.

Source and authorship record

Codex prepared this report with Jamie Stephens’s CAP project materials. The CAP references identify the source snapshot tagged `initial-source`. The source repository is private. Historical results rely on the committed test accounts. The local archive preserves the earlier report, source snapshot, and editorial decisions. Raw historical journals are excluded from that archive and the repository. Upstream links retain the source revisions examined in the earlier surveys. The Claude Code and OpenAI documentation links were checked on September 18, 2026. The September 19 CAP verification record distinguishes new controlled and live checks from the earlier research trials.

References

- [1] C. A. R. Hoare. Communicating Sequential Processes. Prentice Hall International, 1985. Electronic edition, 2004.
- [2] CAP project. CAP publication review. September 19, 2026. Browser authority, distribution notices, and retained findings.
- [3] CAP project. CAP verification. September 19, 2026. Current source, state formats, browser, container, and communication checks.
- [4] CAP project. CAP capability design. Tag `initial-source`, 2026.
- [5] CAP project. Agent manual. Tag `initial-source`, 2026. Operations, environments, recovery, budgets, and context.
- [6] CAP project. Operator runbook. Tag `initial-source`, 2026. External backends, peer access, repositories, and retention.
- [7] CAP project. Distributed situational awareness. Tag `initial-source`, 2026.
- [8] CAP project. Testing records. Tag `initial-source`, 2026. See “Public-source learning: September 14, 2026,” “Subscription compaction recheck,” and “Longer skills and monitoring experiments.”

- [9] CAP project. Watch activity and completion. Tag `initial-source`, 2026.
- [10] CAP project. Tungsten supply-chain CLI test. Tag `initial-source`, 2026.
- [11] CAP project. A CAP case study: continuing research and shared methods. Tag `initial-source`, 2026.
- [12] CAP project. CAP agenda. Updated September 18, 2026, tag `initial-source`.
- [13] CAP project. Advisory observer tests. Tag `initial-source`, 2026. See “Method development and reuse: September 18, 2026.”
- [14] ACE project. ACE source, revision `469a7e301823`. Dependency selected by CAP’s module definition at the report revision.
- [15] CAP project. Compaction survey. September 12, 2026. Pinned implementation comparison and proposed controlled experiments.
- [16] Pi contributors. Pi source, revision `71dca871bc80`, September 11, 2026. See coding-agent compaction and agent loop.
- [17] OpenAI. Codex source, revision `c4017a87aacc`, September 12, 2026. See remote compaction and text compaction.
- [18] Anthropic. How Claude Code works. Official documentation, accessed September 18, 2026. See “The context window” and “When context fills up.”
- [19] OpenCode contributors. CLI session compaction, revision `95daf90670b7`, September 11, 2026.
- [20] Aider contributors. Chat history summarization, revision `5dc9490bb35f`, May 22, 2026. See also coder integration.
- [21] OpenClaw contributors. OpenClaw source, revision `bd2b8414cd7f`, September 14, 2026. See completion admission, child instructions, and prompt reporting.
- [22] CAP project. OpenClaw prompting and agent-management review. September 14, 2026.
- [23] Nico Bailon and contributors. pi-subagents, revision `07bd09e0f93a`, inspected September 18, 2026. See the README and evidence-auditor instructions.
- [24] Wilson Lin. Agent swarms and the new model economics. Cursor, July 20, 2026.
- [25] CAP project. CAP ideas. Tag `initial-source`, 2026. Swarm coordination, model economics, supervision, and continuing assessments.
- [26] Erlang/OTP. Supervisor behaviour. System documentation, accessed September 18, 2026.
- [27] OpenAI. Compaction. API documentation, accessed September 18, 2026.
- [28] CAP project. Agent and process scale test. September 9, 2026 measurements, retained at tag `initial-source`.